SVI Series

Industrial Precision - Flexible and Reliable



The Acculab SVI series scales are economically priced, have a rugged-low profile design and a unique backlit remote display. They are ideal for light industrial applications including shipping, receiving and general weighing applications.

The SVI's indicator can be table or wall mounted (bracket included). It is a snap to install, simple to operate and delivers extremely accurate results. In addition, the large backlit display is easy to read even under dim lighting conditions. The RS-232 data interface is standard and facilitates easy connectivity to a printer, PC or serial device.

Product Description:

- 5 models to choose from: 10kg (22 lbs) to 200kg (440 lbs) capacities
- Remote backlit display in ABS housing, with wall mounting bracket and spiral cable (up to 9 feet or 3 meters in length)
- Applications include: Counting, totaling and unit conversion
- Battery operation available on all models with three selectable auto off modes (4 min., 10 min., always on)
- External calibration with three selectable weight values
- Standard bi-direction RS-232 interface with 8 feet or 2.7 meters of cabling and DB-9 female connector

Product features and highlights:

- Remote backlit LCD display with uniquely designed indicator
- Removable stainless steel low-profile weighing platforms
- Rugged industrial design with more than 200% overload protection
- Three application programs
- Simple operation with external onebutton calibration
- Weighing modes; kg, lb, & ozt (gram weighing also available on SVI-10A & 20B models)
- AC and 9 volt battery operation (power adapter included with all models)
- Low battery, overload, underload and audio tone indicators with auto shutoff



Low profile design with stainless steel pan



Model SVI-100E & SVI-200F with adjustable feet



Large blue backlit display



Included RS-232 interface with cable

Bench and floor scales of the SVI series

Model No.	Capacity	Read- ability	Platform Size	Calibration Weight	Shipping Weight
SVI-10A	22 lbs / 10 kg	0.002 lbs / 1 g	12.4"x12.4" / 308x308 mm	2, 5, 10 kg	14.0 lbs / 6.4 kg
SVI-20B	44 lbs / 20 kg	0.005 lbs / 2 g	12.4"x12.4" / 308x308 mm	5, 10, 20 kg	14.0 lbs / 6.4 kg
SVI-50C	110 lbs / 50 kg	0.01 lbs / 5 g	12.4"x12.4" / 308x308 mm	5, 10, 20 kg	14.0 lbs / 6.4 kg
SVI-100E	220 lbs / 100 kg	0.05 lbs / 20 g	15.9"x20.5" / 403x520 mm	5, 20, 50 kg	42.2 lbs / 19.2 kg
SVI-200F	440 lbs / 200 kg	0.1 lbs / 50 g	15.9"x20.5" / 403x520 mm	5, 20, 50 kg	42.2 lbs / 19.2 kg

Selectable calibration weights not included