


With rugged construction to endure demanding washdown environments, PT stainless steel platform scales provide the ultimate in durability for a variety of commercial, industrial and mining applications. Ideal for weighing food products, chemicals, pharmaceuticals or mining materials, the PT stainless steel platform features an IP66-rated load cell and stainless steel junction box, sealed for protection against water and dust. Easy to clean, the grade 304 stainless steel plate can tolerate frequent washing, while the sleek brushed surface helps prevent the accumulation of food and dirt particles. The PT stainless steel scale is supported by a reinforced frame beneath the platform, allowing the scale to accommodate substantial loads. Offering solid, dependable stability, PT stainless steel's heavy-duty rubber feet are adjustable to compensate for uneven weighing surfaces. Optional ramps are tailor-made to fit the exact size of each platform. PT stainless steel platform can be paired with the AE 403 indicator to provide the features and functions needed for any demanding washdown weighing task.

IP66-rated platform ideal for washdown environments



Features

- Rugged stainless steel construction for ultimate durability
- Approximately three-meter/10-foot shielded cable
- Can be used with any Adam indicators
- Heavy-duty rubber feet ensure stability of unit
- IP66-rated for protection against water and dust



AE 403 Indicator

Applications

- Weighing
- Parts counting
- Checkweighing
- Dynamic / animal weighing
- Percentage weighing
- Display hold
- Peak hold

About ADAM:

For more than 45 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment. Adam provides the right balance of speed, performance and value.

Model	PT 110S	PT 310-5S	PT 310-10S	PT 112S	PT 312-5S	PT 312-10S	PT 115S	PT 315-5S	PT 315-10S	PT 110S [AE403]	PT 310-5S [AE403]	PT 310-10S [AE403]	PT 112S [AE403]	PT 312-5S [AE403]	PT 312-10S [AE403]	PT 115S [AE403]	PT 315-5S [AE403]	PT 315-10S [AE403]
Capacity	2500lb / 1000kg	5000lb / 3000kg	10000lb / 4500kg	2500lb / 1000kg	5000lb / 3000kg	10000lb / 4500kg	2500lb / 1000kg	5000lb / 3000kg	10000lb / 4500kg	2500lb / 1000kg	5000lb / 3000kg	10000lb / 4500kg	2500lb / 1000kg	5000lb / 3000kg	10000lb / 4500kg	2500lb / 1000kg	5000lb / 3000kg	10000lb / 4500kg
Readability	0.5lb / 0.2kg	1lb / 0.5kg	2lb / 1kg	0.5lb / 0.2kg	1lb / 0.5kg	2lb / 1kg	0.5lb / 0.2kg	1lb / 0.5kg	2lb / 1kg	0.5lb / 0.2kg	1lb / 0.5kg	2lb / 1kg	0.5lb / 0.2kg	1lb / 0.5kg	2lb / 1kg	0.5lb / 0.2kg	1lb / 0.5kg	2lb / 1kg
Repeatability (S.D.)	1lb / 0.4kg	2lb / 1kg	4lb / 2kg	1lb / 0.4kg	2lb / 1kg	4lb / 2kg	1lb / 0.4kg	2lb / 1kg	4lb / 2kg	1lb / 0.4kg	2lb / 1kg	4lb / 2kg	1lb / 0.4kg	2lb / 1kg	4lb / 2kg	1lb / 0.4kg	2lb / 1kg	4lb / 2kg
Linearity (+/-)	1lb / 0.4kg	2lb / 1kg	4lb / 2kg	1lb / 0.4kg	2lb / 1kg	4lb / 2kg	1lb / 0.4kg	2lb / 1kg	4lb / 2kg	1lb / 0.4kg	2lb / 1kg	4lb / 2kg	1lb / 0.4kg	2lb / 1kg	4lb / 2kg	1lb / 0.4kg	2lb / 1kg	4lb / 2kg
Excitation Voltage	5 - 10 VAC / DC																	
Loadcells	4																	
Pan Size	39.4"x39.4" / 1000x1000mm		47.2"x47.2" / 1200x1200mm		59.1"x59.1" / 1500x1500mm		39.4"x39.4" / 1000x1000mm		47.2"x47.2" / 1200x1200mm		59.1"x59.1" / 1500x1500mm							
Weighing Units	N/A						g, kg, lb, lb:oz, oz, N, custom unit											
Stabilization Time (sec)	2						2											
Interface	N/A						RS-232											
Calibration	N/A						External calibration											
Display	N/A						Backlit LCD with 1.6" / 40mm -high digits											
Power Supply	N/A						12VDC 800mA adapter / Internal rechargeable battery											
Operating Temperature	-10° to 40°C / 14° to 104°F																	
Housing	Stainless steel																	
Cable Length	10' / 3M																	
Overall Dim.	39.4"x39.4"x4.3" / 1000x1000x110mm (wxdxh)		47.2"x47.2"x4.3" / 1200x1200x110mm (wxdxh)		59.1"x59.1"x4.3" / 1500x1500x110mm (wxdxh)		39.4"x39.4"x4.3" / 1000x1000x110mm (wxdxh)		47.2"x47.2"x4.3" / 1200x1200x110mm (wxdxh)		59.1"x59.1"x4.3" / 1500x1500x110mm (wxdxh)							
Net Weight	136.6lb / 62kg		174.1lb / 79kg		244.6lb / 111kg		136.6lb / 62kg		174.1lb / 79kg		244.6lb / 111kg							

Accessories

Item number	Description
700100203.....	Stainless Steel Ramp - PT 12RS 1200mm wide
700100204.....	Stainless Steel Ramp - PT 15RS 1500mm wide
700100202.....	Stainless Steel Ramp - PT 10RS 1000mm wide
2050013351.....	Indicator stand
700660289.....	Calibration certificate

Supplied by