

# PV Series

## Pocket Scales

### Features

- Multiple Weighing Units (g. oz. dwt. ozt.)
- Fast, Simple Operation
- Standard Calibration Weight
- Sealed Key Panel protects against dust and spills
- Standard Battery Operation (2 AAA included)
- Low Battery Indicator
- Auto Power Off to conserve battery life
- Standard Vinyl Carrying Case
- One Year Warranty

Simple  
Operation

Fits in your  
pocket!

5.3"



Small,  
Compact  
For Easy  
Portability

Fast, Simple  
Calibration

3"

### Specifications

	PV-60	PV-100	PV-200	PV-500
Gram	60 x 0.01	100 x 0.1	200 x 0.1	500 x 0.1
Decimal Ounces	2.1 x 0.001	3.5 x 0.005	7 x 0.005	17.5 x 0.005
Troy Ounce	1.9 x 0.001	3 x 0.005	6 x 0.005	16 x 0.005
Pennyweight	38 x 0.01	77 x 0.1	128 x 0.1	320 x 0.1
Calibration Weight (Standard)	50 ±0.005g	50 ±0.05g	100 ±0.05g	200 ±0.05g
Repeatability/Std. Deviation	±Two display readability			
Linearity	±Two display readability			
Sensitivity Drift	± 50 ppm / °C(10°C ~ 35°C / 50°F ~ 95°F)			
Stability Time	3 seconds (typically)			
Overload Indicator	EE			
Underload Indicator	-EE			
Auto Power Off	Within 10 minutes with no activity			
Operating Temperature	5°C ~ 35°C / 41°F ~ 95°F			
Display Type	5 Digits LCD			
Low Battery Indicator	cb			
Power Requirement	2 AAA size alkaline batteries (standard)			
Typical Battery Life	40 hours with alkaline batteries			
Pan Size	3.25" (W) x 3" (D)			
Dimensions	3" (W) x 5.3" (D) x 0.8" (H)			
Standard Accessories	Calibration Weight, 2 AAA Size Batteries, Vinyl Carrying Case			

Specifications are subject to change without notice.

#### Fax-on-Demand

(800) 726-7099 / (408) 263-0560, Press 2

Document #72

[www.andweighing.com](http://www.andweighing.com)



1555 McCandless Drive  
Milpitas, CA 95035, USA  
Toll Free: (800) 726-7099  
Phone: (408) 263-5333  
Fax: (408) 263-0119