

Advance Features Include:

- ✓ High Accuracy in all Capacities: 10 lb, 20 lb, 50 lb, & 100 lb
- ✓ Optional RS-232 Port
- ✓ Bright Vacuum Fluorescent Displays
- ✓ Limit Mode Feature!
- ✓ Count up to 999,999 pcs
- ✓ Pound / Kilo Conversion

**AC-100 Feature Guide**

- ❑ Rugged design for years of maintenance-free operation
- ❑ Heavy gauge Stainless Steel platter
- ❑ Quick-Response Weight display
- ❑ Add up parts up to 999,999
- ❑ Tough high quality UV-sealed keypad
- ❑ Compact medium-sized footprint design
- ❑ Standard PC-Style removable power cord
- ❑ User-friendly PLU programming
- ❑ Quick operation keypad for high throughput
- ❑ Optional RS-232 port & Interface cable
- ❑ Hi Limit Mode Counting
- ❑ 200 Indirect PLUs



Technical Specifications

Model:	AC-100			
Maximum Capacity:	10.000 lb (5,000 g)	20.000 lb (10,000 g)	50.000 lb (20,000 g)	100.00 lb (50,000 g)
Minimum Graduation:	0.001 lb (0.5 g)	0.002 lb (1 g)	0.005 lb (2 g)	0.01 lb (5 g)
Maximum Tare:	Full Capacity			
Internal Resolution:	100,000 Counts (1/100,000) minimum			
A/D Conversion Rate:	6 Updates / second			
Indirect PLUs:	200 Indirect PLUs			
Vacuum Fluorescent Displays:	Weight:	5 Digits,	99999	(Max Capacity)
	Piece Weight:	6 Digits,	999999	max
	Count:	6 Digits,	999999	max
Platter Size:	Width:	350 mm / 13.8"		
	Length:	270 mm / 10.6"		
Display Designators:	Zero, Net, Stable, Acc, Lack Sample (LS), Lack Unit Weight (LU), lb / g.			
Product Dimensions:	Width:	365 mm / 14.4"		
	Length:	365 mm / 14.4"		
	Height:	160 mm / 4.0"		
Power Requirements:	115 Volts AC @ 60 Hz			

Options

<input type="checkbox"/> RS-232C Interface Board	<input type="checkbox"/> Battery Power Pack
<input type="checkbox"/> RS-232C Cable for PC or Printer	<input type="checkbox"/> Serial Printer (sourced locally)



Acom America Inc.
 404 Paulding Ave.
 Northvale, New Jersey 07647
 Tel: (201) 750-9900
 Fax: (201) 750-7100
 www.acomamerica.com

Distributed by:

*NOTE: Specifications are subject to change without notice.